

# **SELECTING SPRINKLER PACKAGES FOR LAND APPLICATION OF LIVESTOCK WASTEWATER**

Jacob L LaRue  
Senior Engineer  
Cascade Earth Sciences  
Valley, Nebraska  
Voice: 402-359-6041 Fax: 402-359-6081  
Email: jlr1@valmont.com

## **INTRODUCTION**

Livestock operations have changed dramatically in the last ten years. For example the number of hog farms has decreased from 600,000 to 157,000 in the last fifteen years. (Harkin 1998) During this same time the overall output of pork has increased. This increase of size also indicates an increased concentration of animals. Problems associated with any traditional livestock production unit are multiplied as the size increases. Management of the wastewater stream becomes a major component of the management strategy. Maintaining the environmental quality for the area of the livestock operation is critical to the overall success.

Livestock wastes may be applied by a number of methods. Tractor towed manure spreaders or slurry wagons are used to apply to the soil surface. Tractor towed slurry tanks with equipment to 'inject' the waste into the soil are used. Another choice is a plow down system where a tractor tows an injection unit attached to a long hose connected to a pump and the lagoon. On-land application units such as fixed head sprinklers, traveling guns or a center pivots are also commonly used.

Decisions on the type of waste application system are important to the economics of the livestock operation. Timing is one issue, which plays a key role in determining application methods (Hardeman 1997). Most of the methods listed above are only viable in the spring before the crop is planted or in the fall after it is harvested. Center pivots are not however limited by whether a crop is present or not as they may be used to apply over an active crop.

Center pivots, due to their characteristics, are considered to have advantages with regards to applying livestock wastes, particularly from a lagoon with large amounts of water to handle. Some of these characteristics include limited labor input required, application uniformity, ease in handling large quantities of effluent

and particularly the ability to apply to actively growing crops with minimal negative impact to the crop.

Operators readily invest in major capital improvements and equipment to facilitate the production of meat or milk by providing the best possible environment for the animals. However most producers have a strong reluctance to invest in more than the minimum required to meet existing local, state and federal environmental regulations for disposal of the wastewater. If the investment does not add value to their operation - why make the expenditure?

## **DISCUSSION**

Land application of wastewater with center pivot and linear irrigation equipment has been used for more than thirty years. Until the late 1970's the land application package was easy to select, as the choices were limited to relatively high-pressure impact sprinklers (50psi) or the Valley Slurry Shooter™ using high volume sprinklers (90psi). Since the early 1980's the equipment and techniques for irrigating with fresh water have changed dramatically to the point the pressures at the nozzle inlet may be as low as 6psi. Currently more than five major classes of sprinkler packages are being used with many options within each class – pad styles being the main option. In many cases both water for reuse and fresh water are applied with the same equipment. Midwest Plan Service's MWPS-30 (MWPS, 1999) discusses general principles in sprinkler selection relating to fresh water application but does not attempt to quantify any procedure or specifically look at effluent application. Other publications have provided general discussions without offering a specific procedure – Livestock Waste Facilities Handbook (MWPS, 1993), Liquid Manure Application Systems Design Manual (NRAES, 1998) and Agricultural Waste Management Field Handbook (USDA, 1992)

Then also in today's world one must take into account the issues and public perception of land application systems. Land application of wastes may be imposing in some locations, potentially dangerous conditions relative to environmental quality (Hegde 1997). We must insure any equipment being used for land application meets public scrutiny.

## **OBJECTIVE**

How does one select the optimum sprinkler package for a particular waste water situation?

## **DISCUSSION**

Currently many sprinkler packages are selected by irrigation dealers and customers based on personal experience and preference. Some of these general sprinkler categories are:

<u>type</u>	<u>orifice diameters</u>	<u>pad</u>	<u>pressure</u>
drag hose	4/64 to 24/64in	none	6 to 10psi
fixed pad	4/64 to 24/64in	fixed	6 to 20psi
rotating pad	4/64 to 24/64in	rotating	15 to 30psi
impact	9/64 to 40/64in	n/a	40 to 60psi
high volume guns	0.50 to 0.94in	N/A	45 to 90psi

A systematic approach does not exist to assistance in the decision making process. Experience has taught that "if it worked the last time, it should work again" or "that is what my neighbor's doing".

It is recommended looking at each system individually to make the selection on the best information available.

To begin the process information is required about the particular application:

- Material being applied
  - Estimated solids content
  - Organic material
  - Inorganic material
  - Particle size
- Environmental constraints
  - Ground water wells
  - Neighbors
  - Tile line
- Management issues
  - Operating costs
  - Energy costs
  - Maintenance
- CAFO permit constraints

Then look at how the wastewater stream is handled –

- Collection
- Treatment (if any)
- Storage
- Pump system
- Position of inlet of the pump

We have tried to develop a quantitative approach to the selection of a recommended sprinkler package based on the information collected. To do this we apply the information to a ranking system

First assign 1-5 points for each item based on the headings –

Value to assign	1	2	3	4	5
<u>Item</u>	<u>Range</u>				
1 - Solids content	<0.5%	1.0%	2.0%	3.0%	>4.0%
2 - Particle size	small		medium		large
3 - Pump impeller	closed		semi open		open
4 - Pump inlet	floating				bottom
5 - Labor costs	low		medium		high
6 - Energy costs	high		medium		low
7 - Environment	high		medium		low
8 - Storage	2 stage Lagoon		1 stage lagoon		pit
9 - Collection	flushing				scraper
10 – Pump style	fresh water		slurry		chopper
11 – Uniformity (CU)	85		75		65
	Minimum number of possible points –		11		
	Maximum number of points -		55		

This is the range within which to work with the lower the number tending to indicate a wastewater stream, which has limited solids content and small particles. The closer a number approaches 55 the thicker the wastewater and larger the particles.

Some of the items are relatively easy to estimate – others such as the solids content are very difficult. The following table is one way to characterize the solids in a waste stream.

First visualize a bucket with the manure in it. Then start tipping the bucket -

<u>Angle from ground</u>	<u>how it flows</u>	<u>estimated solids</u>
45 degrees above	smooth stream	1 to 2%
30 degrees above	in small globs	3%
15 degrees above	in quarter sized globs	4%
0 degrees, bucket parallel to ground	fist sized globs	5%

45 degrees, pouring down

thick chunks

6%

This table allows a method to roughly estimate the solids content based on how the effluent flows.

Using the point total one goes into the table to select a recommended sprinkler type.

Point Total	Type	Pad	Pressure
10 to 19	low pressure on drops	fixed	6 to 20psi
20 to 29	low pressure on drops	rotating	15 to 30psi
30 to 39	impact	n/a	40 to 60psi
40 to 50	high volume guns	n/a	45 to 90psi

A worksheet was developed to allow a person to 'fill-in-the blank' with the data and information collected. One does the best to estimate and make a selection based on experience and quantitative data if available.

## Sprinkler Selection Worksheet

### Item Ranking

- |   |         |       |
|---|---------|-------|
| 1) -Solids content – _____ consistency  | _____ % | _____ |
| 2) Particle size _____ inches           |         | _____ |
| 3) Pump impellor _____                  |         | _____ |
| 4) Pump inlet _____                     |         | _____ |
| 5) Labor costs _____ \$/hr              |         | _____ |
| 6) Energy costs _____ ¢/kw-hr or gallon |         | _____ |
| 7) Environment _____ issues             |         | _____ |
| 8) Storage _____                        |         | _____ |
| 9) Collection _____                     |         | _____ |
| 10) Pump style _____                    |         | _____ |
| 11) Uniformity _____                    |         | _____ |
| Total Points                            |         | _____ |

<u>Ranking</u>	<u>type</u>	<u>pad</u>	<u>pressure</u>
11 to 19		fixed	6 to 20psi
20 to 29		rotating	15 to 30psi
30 to 39	impact	n/a	40 to 60psi
40 to 55	high volume guns		45 to 90psi

Sprinkler package selected – \_\_\_\_\_

Pad type if applicable – \_\_\_\_\_

Pressure selected - \_\_\_\_\_

## Testing of the selection process

**Example 1** - Single stage dairy lagoon, limited labor, no neighbors within two miles, flushing system, wants to pump from bottom, is not nutrient limited. Primarily system to be used for land application and not irrigation.

### Item

### ranking

1) Solids content –	thick consistency	4%	4
2) Particle size	3/16 inches	(pieces of corn cob)	4
3) Pump style	slurry		4
4) Pump impellor	semi open		3
5) Pump inlet	on bottom of lagoon		5
6) Labor costs	9.25 \$/hr		4
7) Energy costs	4.25 ¢/kw-hr	or gallon	2
8) Environment	no issues		5
9) Collection	flushing		1
10) Storage	pit		5
11) Uniformity	low		<u>5</u>
Total Points			42

<u>Ranking</u>	<u>type</u>	<u>pad</u>	<u>pressure</u>
10 to 19		fixed	6 to 20psi
20 to 29		rotating	15 to 30psi
30 to 39	impact	n/a	40 to 60psi
40 to 50	high volume guns		45 to 90psi

Sprinkler package selected

minimum of impact sprinkler, hig volume gun suggested

Pad type if applicable -

Not applicable to impact or volume guns

Pressure selected –

Minimum suggested of 45psi

**Example 2** - two stage hog lagoon, limited labor, no neighbors within two miles, plug/pull system, wants to pump from top w/ floating pump, wants no problem with plugging and will use for irrigation

<b>Item ranking</b>		
1) Solids content – thin	<.5%	1
2) Particle size	3/16 inches (trash in lagoon, in-organics)	4
3) Pump style	fresh water	1
4) Pump impellor	closed	1
5) Pump inlet	on top of lagoon	1
6) Labor costs	20.00 \$/hr	4
7) Energy costs	2.25 ¢/kw-hr or gallon	2
8) Environment	no issues	5
9) Collection	flushing	1
10) Storage	two stage lagoon	1
11) Uniformity	high	<u>1</u>
<b>Total Points</b>		<b>22</b>

<u>Ranking</u>	<u>type</u>	<u>pad</u>	<u>pressure</u>
10 to 19		fixed	low
20 to 29		rotating	low to medium
30 to 39	impact	n/a	medium to high
40 to 50	high volume guns		high

Sprinkler package selected

From ranking – rotating pad

But customer suggestions wants no problems

A combination system may be the best choice. Utilizing the wider spacing of the sprinklers with rotating pads for the first portion of the center pivot until a larger nozzle size is reached.



## **SUMMARY**

The model has proved to be successful in the actual situations where it has been applied as a decision tool. This process is not perfect and one must apply reasonable judgement in selecting a sprinkler package. Also the process is only as good as the data which is collected. As with any tool care must be taken to consider all factors and apply appropriately.

In addition center pivots can successfully be used to meet requirements for minimizing environmental impact of spray drift and runoff and also meet customer requirements for monitoring and reporting by the selection of equipment options.

Livestock systems continue to evolve. Rations, genetics and housing systems have changed significantly in the last five years. Feeding and manure handling systems continue to change. As production units change the irrigation industry is working on equipment to continue to meet customer's requirements.

Center pivots continued to be an accepted option for land application of wastewater generated from a CAFO particularly if a lagoon or storage reservoir is used. This type of equipment provides the control and monitoring capabilities required by many CAFOs (LaRue 1998).

In many cases the CAFO may have different constraints from traditional farm livestock units. In these cases, alternative treatment such as the Sheaffer MRRS, (Sheaffer, 1998) anaerobic digestion or other methods may need to be utilized to reduce the nutrient, odor and sludge. Once the treatment process is completed, the remaining liquid fraction may be land applied with a center pivot or other system designed to handle large volumes of low nutrient strength water.

As is always the case the operator must be aware and follow local and state regulations.

## **REFERENCES**

Dougherty, Mark, Geohring, Larry, Wright, Peter, *Liquid Manure Application Systems Design Manual*, NRAES-89, Northeast Regional Agricultural Engineering Service, Cornell University Ithica NY, 1998

Gilley, James R., 1983, *Suitability of Reduced Pressure Center Pivots*, Journal of Irrigation and Drainage Engineering, Vol 110, No. 1,

Hardemann, T.L., Mickelson, S.K., Baker, J.L., Kanwar, R.S., Lorimor, J.C., Melvin, S.W., 1997 *Effects of Rate, Method, and Timing of Swine Manure Application on Groundwater Quality*, 1997 International Summer Mtg. of ASAE, Paper 97-2145, Minneapolis Minnesota

Harkin, Tom, 1997 report on animal waste issues, The District Leader January 1998

Hegde, Poornima and Kanwar, R.S., 1997 *Impact of Manure Application on Groundwater Quality*, 1997 International Summer Mtg. of ASAE, Paper 97-2144, Minneapolis Minnesota

Kifco / Ag-Rain, Havana, Illinois

LaRue, J L, Howard, H D and Dorsett, W E, *The Use of Center Pivots to minimize Enviromental Impact of Land Applied Swine Manure*, 1998 International Summer Mtg. of ASAE, Paper 98-2113, Orlando Florida

LaRue and Howard, 1998, *Modification and Testing of Commercial Center Pivots to Apply Dairy Waste Slurries and Meet EQIP Program Requirements*, 1998 International Summer Mtg. of ASAE, Paper 98-2100, Orlando, Florida

Midwest Plan Service, *Sprinkler Irrigation Systems*, MWPS-30, 1<sup>st</sup> edition, 1999, Ames Iowa

Midwest Plan Service, *Livestock Waste Facilities Handbook*, MWPS-18, 3<sup>rd</sup> edition, 1993, Ames Iowa

Northeast Regional Agricultural Engineering Service, *Liquid Manure Application Systems Design Manual*, NRAES-89, 1998, Ithaca, New York

Sheaffer, Jack, Anderson, Paul, Ellis, Stuart and Johnson, John, *Enviormentally Friendly Manure Treatment for Large Scale Confined Animal Feeding Operations*, 1998 *Animal Production Systems and the Environment*, Des Moines Iowa

United States Department of Agriculture, *Agricultural Waste Management Field Handbook*, Part 651, 1992, Washington DC

Valmont Industries Inc., *Livestock Waste Management through Center Pivots*, Wastewater Intelligence volume 1, AD10182 1988